

Unikaccroche

Concentrated adhesion resin

DESCRIPTION :

Unikaccroche is an aqueous dispersion resin made from silica whose purpose is to heighten adhesion power of **Unikofloor®** coatings on very smooth or porous surfaces. Moreover, thanks to its silica base, **Unikaccroche** considerably improves adhesion of glues found on the market.

USAGE :

Unikofloor® can be applied to all indoor substrates such as concrete, plasterboards, tiles, plaster, terra cotta, earthenware, paint...

CHARACTERISTICS :

PH : 7.3

Density : 1.2

Quantity : 100 to 150 gr per m² according to substrate.

Kits : 5Kg – 2.5Kg-1 Kg

Implementation temperature : + 18°C to 30°C

Implementation humidity : from 40% to 75%

Store products away from freezing and high temperatures.

To clean tools : water.

Security sheet on demand at : +33 559412571

This technical sheet replaces and supercedes all previous ones concerning the product.

The information contained in this present leaflet is the expression of our knowledge and of results obtained through tests run in order to ever remain objective. The following cannot however be considered either as guarantee or an engagement of our company's responsibilities in the case of faulty application as all manipulation and implementation of our product is beyond our control. We strongly recommend, in order to guarantee proper usage of our product to take part in our approved training courses run by our teams. To ensure that the product properly applies to the situation, the user must carry out tests beforehand.

Unikaccroche

Concentrated adhesion resin

APPLICATION :

Unikaccroche is applied in one thin layer with a splater brush or roller. Make sure to mix resin thoroughly with the sand which sediments at the bottom of the jerry can. Once dried, the product should present a rough surface.

Wait 4 hours before applying coating. It must be dry to touch.

It must not be applied to substrate if there is a risk of freezing in the following 24 hours.

Warning: it is imperative to maintain a minimum application temperature of 18 °C with maximum humidity of 75 %. If this not the case, the necessary must be done to reach application criteria.

REQUIRED PROTECTION

Appropriate personal protection and security gear must be used: vinyl gloves and protection glasses.

Security sheet on demand at : +33 559412571

This technical sheet replaces and supercedes all previous ones concerning the product.

The information contained in this present leavlet is the expression of our knowledge and of results obtained through tests run in order to ever remain objective. The following cannot however be considered either as guarantee or an engagement of our company's responsibilities in the case of faulty application as all manipulation and implementation of our product is beyond our control. We strongly recommend, in order to guarantee proper usage of our product to take part in our approved training courses run by our teams. To ensure that the product properly applies to the situation, the user must carry out tests beforehand.