

## Unikochape

### Seals pores in screeds before using Epoxy S.

#### DESCRIPTION:

**Unikochape** is a resin with an aqueous phase which has the ability of sealing porous floors before applying Epoxy S on liquid cement or anhydride screeds. It enables to economise Epoxy S or avoids having to apply a second layer of epoxy. It also heightens grip power between screed and epoxy S.

#### CHARACTERISTICS :

White liquid

PH 7.2

Density 1.05

Amount : 80 gr per m<sup>2</sup> according to quality of screed.

Temperature use : + 18°C to 30°C

Humidity : 40 % to 75 %

Store products away from freezing and high temperatures.

To clean tools : water.

#### APPLICATION :

**Unikochape** is applied with spalter brush or microfibre.

Ensure substrate be dry, clean, smooth and free of residue.

**DRYING** : Wait 1 to 2 hours before applying epoxy S following appropriate technical sheet instructions.

#### REQUIRED PROTECTION

Appropriate personal protection and security gear must be used : vinyl gloves and protection glasses.

Security sheet on demand at : +33 559412571

This technical sheet replaces and supercedes all previous ones concerning the product.

The information contained in this present leavlet is the expression of our knowledge and of results obtained through tests run in order to ever remain objective. The following cannot however be considered either as guarantee or an engagement of our company's responsibilities in the case of faulty application as all manipulation and implementation of our product is beyond our control. We strongly recommend, in order to guarantee proper usage of our product to take part in our approved training courses run by our teams. To ensure that the product properly applies to the situation, the user must carry out tests beforehand.